

Epson WorkForce Pro EM-C800

- PrecisionCore Heat-Free Technology simple, smart and clean solution that delivers outstanding quality with low waste
- Energy efficient low power consumption
- Powerful business productivity print speed of 25 ISO ppm¹ (mono/colour);
 fast first page out time of 4.8 sec and zero warmup time
- Engineered for reliable performance recommended monthly print volume of up to 5,000 pages
- Remarkable image quality DURABrite™ Ultra, replaceable ink pack system (RIPS) delivers vivid colour and crisp black text
- Robust security full suite of advanced security features
- Compatible with Epson Solutions Suite and industry-leading third-party solutions – Epson Open Platform for seamless workflow integration
- Intuitive operation 4.2" colour touchscreen
- Minimal user intervention replaceable ink pack system with extra high-capacity packs lets you print up to 50,000 ISO pages mono / 20,000 ISO pages colour²

Epson WorkForce Pro EM-C800

n Remote Print, Epson Smart Service, Microsoft® Universal ISO cpm (colour)	Paper formats Input paper capacity Output tray capacity Automatic 2-sided scan / copy / fax CONNECTIVITY Standard connectivity	A4 (210 mm x 297 mm), A5 (148 mm x 210 mm), A6 (105 mm x 148 mm), B5, B6, C4 (envelope), C6 (envelope), DL (envelope), No. 10 (envelope), letter, legal 90 x 130 mm, 100 x 150 mm, 130 x 180 mm, 16:9, HLT, EXE, user defined 250 sheets plain paper (250 sheets plain paper x 1 tray); rear feed: 80 sheets (1,830 sheets total with three optional 500-sheet paper trays); No. 10 envelopes 150 sheets Yes Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet (1000 Base-T/100 Base-TX/10 Base-T), Wi-Fi Direct®
Service, Microsoft® Universal Service (Microsoft® Universal Service (Microsoft® Universal	Output tray capacity Automatic 2-sided scan / copy / fax CONNECTIVITY	250 sheets plain paper (250 sheets plain paper x 1 tray); rear feed: 80 sheets (1,830 sheets total with three optional 500-sheet paper trays); No. 10 envelopes 150 sheets Yes Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet
Service, Microsoft® Universal Service, Microsoft® Universal Service, Microsoft® Universal	Automatic 2-sided scan / copy / fax CONNECTIVITY	150 sheets Yes Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet
Service, Microsoft® Universal Service, Microsoft® Universal Service, Microsoft® Universal	Automatic 2-sided scan / copy / fax CONNECTIVITY	Yes Hi-speed USB (compatible with USB 2.0 specification), Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet
ISO cpm (colour)		Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet
, , ,	Standard connectivity	Wireless LAN IEEE (802.11 b/ g/n/ac), Wired Ethernet
		(.555 5400 1/100 5400 1/4 10 5400 1/1, WI I I DII 001
esize, ID copy, collate, adjustable inched holes, remove shadows	Operating systems	Windows® 11, Windows 10 (32-bit, 64-bit), Windows 8, 8.1 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Server® 2008, 20126 — Windows Server 2016, 2019, 20226, Mac®OS X® 10.9.5 — macOS® 14.x7
sided ADF	GENERAL	
1	Display	4.2" colour touchscreen
dpi	Temperature	Operating: 10°C to 35°C, Storage: -20°C to 40°C
	Noise level	36 dB
	Rated voltage / frequency	AC 100 V - 240 V / 50 Hz - 60 Hz
nt Capture Pro, scan to cloud ⁵ ,	Power consumption (approximate)	Standalone copy printing: 30 W Ready mode: 13.8 W Sleep mode: 1.1 W TEC rating: 0.18 kWh / week
,	Weight and dimensions	Main unity 01 0 kg, 405 mm v 505 mm v 410 mm
lour ((W x D x H)	Main unit: 21.3 kg. 425 mm x 535 mm x 413 mm
x. 3 sec / page	Software available ⁸	Epson printer driver, PCL 5 driver emulation ⁹ , PCL 6 driver emulation ⁹ , Adobe® PostScript® 3™
ı	Epson Solutions Suite	Epson Device Admin, Epson Print Admin, Epson Print Admin Serverless, Epson Remote Services
	etwork folder, memory device,	Rated voltage / frequency uplex 60 ipm Int Capture Pro, scan to cloud ⁵ , etwork folder, memory device, so lour Int Capture Pro, scan to cloud ⁵ , etwork folder, memory device, so Weight and dimensions (W x D x H) Software available ⁸ Enson Solutions Suite

- 4 Based on 200 dpi, letter-size (215.9 mm x 279.4 mm), in mono or colour.
- 5 Requires an internet connection, a free Epson Connect account and a destination email address or cloud storage account. For a list of supported cloud services, visit www.epson.com.au/connect
- 6 Only printing and scanning are supported under Windows Server OS.
- 7 Some applications and/or functions may not be supported under Mac OS X.
- 8 Internet access is required to download and install drivers and software.
- 9 Not all media types are supported for PCL printing.

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice with customers recommended to check with the Epson AU/NZ websites for latest details.





Epson New Zealand www.epson.co.nz

12/2024

EPSON

¹ Mono and colour print speeds are measured in accordance with ISO/IEC 24734. Actual print times will vary based on factors including system configuration, software and page complexity. For more information, visit www.epson.com.au/printspeed/

² Replacement ink pack yields are estimated based on ISO/IEC 24711 test in default mode printing continuously. Ink pack yields vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour.

³ Mono and colour copy speeds are determined in accordance with ISO/IEC 29183. Actual copy times will vary based on factors including system configuration, and page complexity. For more information, visit www.epson.com.au/printspeed/